



## Specification

<b>Model No.:</b>	RS-LS9W60(88431) / RS-LS12W60(88431)
<b>Front cover &amp; Housing:</b>	Aluminum body
<b>Dimensions:</b>	D60*H320mm(Max.); D60*H103mm(Min.)
<b>Tempered Glass:</b>	3mm thickness
<b>LED chip:</b>	Cree
<b>LED Q'ty:</b>	1pc 9W LED / 1pc 12W LED
<b>Cable gland:</b>	Nickel plated brass PG9
<b>Driver:</b>	Constant current driver
<b>Lens:</b>	Reflector
<b>Beam Angle Options:</b>	15° 24° 38°
<b>Power Cable:</b>	3*0.75mm <sup>2</sup> VDE rubber cable
<b>Protection Class:</b>	IP65
<b>Environment:</b>	Dry
<b>Mounting Hardware:</b>	Wall, ceiling, floor, pole mounting
<b>Net Weight:</b>	0.85kgs with 1m cable
<b>Lifetime:</b>	>50000H

## Order information

Item code	Color	Light source(w)	Line Way	Input Voltage (v)	Operating current (mA)	Consumption (w)	Luminous (lm)
88431.091.01	2700-3000K	1*9	L/N/G	AC90-230	40-80	9	990
88431.091.02	4000-4500K	1*9	L/N/G	AC90-230	40-80	9	1035
88431.091.03	5000-5500K	1*9	L/N/G	AC90-230	40-80	9	1080
88431.121.01	2700-3000K	1*12	L/N/G	AC90-230	54-109	12	1320
88431.121.02	4000-4500K	1*12	L/N/G	AC90-230	54-109	12	1380
88431.121.03	5000-5500K	1*12	L/N/G	AC90-230	54-109	12	1440

