




Product Size



Specification

| | |
|-----------------------------------|---|
| Model No.: | RS-FT27W316X(88103) / RS-FT24W316X(88103) |
| Front cover & Housing: | Stainless steel 316L |
| Dimensions: | D160*H36mm (Nozzle hole size: 47mm) |
| Tempered Glass: | 5mm thickness |
| LED chip: | CREE |
| LED Q'ty: | 9pcs 3W LED / 6pcs 4in1 LED |
| Cable gland: | Stainless steel 316L PG13.5 |
| Driver: | Constant current driver |
| Lens: | Clear, Bead, Frosted |
| Beam Angle Options: | 10° 20° 30° 45° 60° 90° |
| Power Cable: | AWG 5/18 or AWG 3/18 SOW rubber cable |
| Protection Class: | IP68 |
| Environment: | Dry / Submerged |
| Mounting Hardware: | Surface Mounted System / Nozzle fixed |
| Net Weight: | 2.5kgs with 1.5m cable |
| Lifetime: | >50000H |

Order information

| Item code | Color | Light source(w) | Line Way | Input Voltage (v) | Operating current (mA) | Consumption (w) | Luminous (lm) |
|--------------|----------------------------|-----------------|------------------|-------------------|--|------------------------------|--------------------------------------|
| 88103.093.01 | 2700-3000K | 9*3 | V+/V- | AC/DC12-24 | 2250 / 1125 | 27 | 1260 |
| 88103.093.02 | 4000-4500K | 9*3 | V+/V- | AC/DC12-24 | 2250 / 1125 | 27 | 1332 |
| 88103.093.03 | 5000-5500K | 9*3 | V+/V- | AC/DC12-24 | 2250 / 1125 | 27 | 1395 |
| 88103.093.04 | 6000-6500K | 9*3 | V+/V- | AC/DC12-24 | 2250 / 1125 | 27 | 1395 |
| 88103.093.05 | Red | 9*3 | V+/V- | AC/DC12-24 | 1500 / 750 | 18 | 315 |
| 88103.093.06 | Green | 9*3 | V+/V- | AC/DC12-24 | 2250 / 1125 | 27 | 810 |
| 88103.093.07 | Blue | 9*3 | V+/V- | AC/DC12-24 | 2250 / 1125 | 27 | 360 |
| 88103.093.08 | Yellow | 9*3 | V+/V- | AC/DC12-24 | 2250 / 1125 | 27 | 855 |
| 88103.093.09 | RGB-DMX512 (3 channel) | 9*3 | V+ /V-/D+/D-/GND | AC/DC12-24 | R: 500 / 250 B: 750 / 375 G: 750 / 375 | R: 6 B: 9 G: 9 | R: 105 B: 120 G: 270 |
| 88103.093.10 | Auto changing color | 9*3 | V+/V- | AC12-24 | R: 500 / 250 B: 750 / 375 G: 750 / 375 | R: 6 B: 9 G: 9 | R: 105 B: 120 G: 270 |
| 88103.093.12 | RGBV+ (build-in CC driver) | 9*3 | R/G/B/V+ | DC12-24 | R: 500 / 250 B: 750 / 375 G: 750 / 375 | R: 6 B: 9 G: 9 | R: 105 B: 120 G: 270 |
| 88103.064.13 | RGBW-DMX512 (4 channel) | 6*4in1 | V+ /V-/D+/D-/GND | DC24 | R: 250 B: 250 G: 250 W: 250 | R: 6 B: 6 G: 6 W: 6 | R: 150 B: 180 G: 360 W: 540 |

