



## Specification

<b>Model No.:</b>	RS-WW36W-B(88304)
<b>Front cover &amp; Housing:</b>	Aluminum body
<b>Dimensions:</b>	L1000*W45*H62mm(H105mm with bracket)
<b>Tempered Glass:</b>	3mm thickness
<b>LED chip:</b>	Epistar
<b>LED Q'ty:</b>	36pcs 1W LED
<b>Cable gland:</b>	Nickel plated brass PG9
<b>Driver:</b>	Constant current driver
<b>Lens:</b>	Clear, Bead, Frosted
<b>Beam Angle Options:</b>	10° 30° 45° 60° 90°
<b>Power Cable:</b>	2*1.0mm <sup>2</sup> / 3*0.75mm <sup>2</sup> / 4*0.75mm <sup>2</sup> / 2*1.0mm <sup>2</sup> +3*0.75mm <sup>2</sup> VDE rubber cable
<b>Protection Class:</b>	IP65
<b>Environment:</b>	Dry
<b>Mounting Hardware:</b>	Wall Mounted System
<b>Net Weight:</b>	2.8kgs with 1m cable
<b>Lifetime:</b>	>50000H

## Order information

Item code	Color	Light source(w)	Line Way	Input Voltage (v)	Operating current (mA)	Consumption (w)	Luminous (lm)
88304.361.01	2700-3000K	36*1	V+/V- or L/N/G	DC24, AC90-230	1500 / 163-327	36	3240
88304.361.02	4000-4500K	36*1	V+/V- or L/N/G	DC24, AC90-230	1500 / 163-327	36	3420
88304.361.03	5000-5500K	36*1	V+/V- or L/N/G	DC24, AC90-230	1500 / 163-327	36	3600
88304.361.04	6000-6500K	36*1	V+/V- or L/N/G	DC24, AC90-230	1500 / 163-327	36	3600
88304.361.05	Red	36*1	V+/V- or L/N/G	DC24, AC90-230	1500 / 163-327	36	900
88304.361.06	Green	36*1	V+/V- or L/N/G	DC24, AC90-230	1500 / 163-327	36	2160
88304.361.07	Blue	36*1	V+/V- or L/N/G	DC24, AC90-230	1500 / 163-327	36	1080
88304.361.08	Yellow	36*1	V+/V- or L/N/G	DC24, AC90-230	1500 / 163-327	36	2520
88304.361.09	RGB-DMX512 (3 channel)	36*1	V+/V- /D+/D-/GND	DC24	R: 500 G: 500 B: 500	R: 12 G: 12 B: 12	R: 300 G: 720 B: 360
88304.361.10	Auto changing color	36*1	V+/V-	AC24	R: 500 G: 500 B: 500	R: 12 G: 12 B: 12	R: 300 G: 720 B: 360
88304.361.12	RGBV+ (build-in CC driver)	36*1	R/G/B/V+	DC24	R: 500 G: 500 B: 500	R: 12 G: 12 B: 12	R: 300 G: 720 B: 360

